

Maintenance of domestic timber floors



Bona®

Phone 1300 882 806



Bona products have been protecting and maintaining timber floors worldwide for over 90 years. An important part of the Bona system is the ongoing care and maintenance of the floor. The following information will help you keep your timber floor in good condition and looking great.

Prevention

Preventative measures are very important in maintaining timber floors. Install a good quality mat both inside and outside of external doors. Mats should be as large as possible and able to remove both grit and moisture.

Whenever possible remove your shoes. This will help reduce the amount of dirt brought into the property and potential impact damage from stilettos. In very heavily trafficked areas, such as entrance halls and kitchens, the use of mats should be considered to reduce surface wear. Rugs should be permeable to allow the floor to 'breathe'.

Use felt protective feet on all furniture legs / bases to prevent damage. Similarly make sure that pet's claws are regularly trimmed to reduce the possibility of scratches and indentation.

Wipe up all spillage immediately it is noticed. Animal urine, cooking fats, and other similar materials can damage the floor if left on the surface for any length of time. This may result in permanent staining in some cases.

Cleaning

Clean the floor regularly using dry cleaning methods. Suitable methods include the Bona Spray mop system with the Bona Dusting pad, soft broom or vacuum with a soft brush attachment. Regular removal of surface dirt and sand will prevent the surface from being scratched.

To remove water soluble dirt, clean using Bona Wood Floor Cleaner. First dry clean the floor to remove surface dirt, etc. Spray the surface sparingly with Wood Floor Cleaner and clean using the Bona Microfibre Cleaning pad. The mop should be used along the boards wherever possible. Rinse the Cleaning pads regularly in clean water during use and replace when dirty. The pads can be washed in a washing machine after use.



Bona®

Phone 1300 882 806

Never wet mop a timber floor. Excessive quantities of cleaner / water may damage the floor by causing it to swell, lifting the board edges and leaving the surface uneven. It may also lead to cleaning product residues remaining on the floor after it has been cleaned resulting in a hazy discolouration being evident.

Avoid using household cleaners or polishes on the floor as they may damage the finish and make overcoating more difficult in the future

Maintenance

If areas of the floor begin to look slightly dull in comparison to the remainder the use of Bona Wood Floor Refresher should be considered. Bona Refresher is designed to restore an even sheen to the floor whilst giving added protection to the surface against future traffic. Most importantly though, floors maintained using Bona Refresher can be refurbished in the future without having to be sanded back to bare timber. Please note that domestic staircases have a specific requirement for slip resistance and Bona Refresher should not be used on stair treads.

Thoroughly clean the floor using Bona Wood Floor Cleaner. Allow the surface to dry. NB. It is very important that the floor is clean as any deposits of dirt, etc. will become trapped beneath the layer of Bona Refresher and will remain visible.

Apply an even application of Bona Refresher, with the boards, using the Bona Applicator pad on the Bona Mop. Detailed instructions may be found in the product datasheet. After 2 hours the floor may be trafficked and put back into normal use although the replacement of rugs, furniture etc. should be avoided for 24 hours. It is important that the whole floor is treated rather than small areas. Trying to coat small areas will result in a visible difference in sheen level between the coated and uncoated parts of the floor.

NB. the sheen level may increase with repeated use of Bona Refresher on low sheen floors. Bona Refresher should not be used on Bona Traffic HD Anti Slip, Extra Matt or Bona Traffic Natural.

Refurbishment

Regular maintenance of a floor will extend the time before refurbishment is required. Refurbishment of timber flooring is usually related to appearance issues from damage such as scratches or indentations rather than wear. This type of damage can be controlled using preventative measures but inevitably over time the appearance of the surface will deteriorate.

Ideally the application of an additional coat of a Bona finish will be carried out before the floor is damaged to a point where a complete refinishing process is required. To refurbish the floor usually all which is required is to thoroughly clean and prepare the surface in accordance with Bona's overcoating instructions before applying an application of the appropriate finish.

For additional information regarding floor care and floor care products please visit www.bona.com.au